



Temperature range: **+4°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Name	PASTELLA SWEET 0.6W	PASTELLA SWEET 0.9W	PASTELLA SWEET 1.3W
Code	PSTS60W	PSTS90W	PSTS130W
Length [mm]	660	960	1360
Height [mm]	1200+/-10	1200+/-10	1200+/-10
Depth [mm]	850	850	850
Capacity [dm ³]	215	395	582
Display area [m ²]	0.9	1.2	1.8
Total Display Area (TDA) [m ²]	-	-	-
Temp. range [°C]	(+4 ± +10°C)	(+4 ± +10°C)	(+4 ± +10°C)
Temp. class	-	-	-
Climate class	-	-	-
Energy efficiency class	D	D	D
Refrigerant	R290	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	-	-	-

Standard equipment

internal cooling aggregate R290

openable front glass with bending radius R20

dynamic cooling with automatic defrost

external housing made of coated steel sheet in a colour from the (IGLOO pattern book)

side panels made of melamine plate - different colors available (IGLOO pattern book)

wooden melamine front panel - different colors available (IGLOO pattern book)

ecological polyurethane foam insulation

3 pcs of glass exposition shelves with height and angle adjustment placed on the frame

internal frame painted - different colors available (IGLOO pattern book)

bottom shelf made of painted steel - different colors available (IGLOO pattern book)

upper interior lighting + backlight of each shelf LED

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

device prepared for multiplexing (mod/A)

bottom shelf made of stainless steel

bottom shelf made of stainless steel

wooden front panel made of veneer or TREND - different colors available (IGLOO pattern book)

wooden sides panel made of veneer or TREND - different colors available (IGLOO pattern book)

electronic temperature recorder + software

temperature recorder wire

set of wheels (castors)

humidity control system

